CERÁMICAS CALAF S.A.U

PRODUCT SHEET




11970

MANUFACTURER: CERÁMICAS CALAF, S.A.U

Locality: 08280 CALAF (Barcelona)

Date: 01-01-2025

P.S.



Dimensions in mm.

SERIES	CADI RUSTICO
PRODUCT DESIGNATION	PELDAÑO 27x31x1.6 cm. BIS.

Natural extruded ceramic tile (not glazed), under Annex C Part 2, 3%<E<6%, Group AII_{a-2} of the Standard EN-14411:2003

For internal and/or external floorings

Characteristics	Declared value		Tests
Dimensions	Longth	270 mm	UNE-EN ISO
	Length Width		
		310 mm 16 mm	
D' ' 1, 1	Thickness	-	
Dimensional tolerances	Average of each tile	± 2% and	
Length and width (1)	A	max. 4 mm	
	Average of ten tiles	± 1.5%	
Dimensional tolerances - Thickness (1)	Average of each tile	± 10%	10.545-2
Straightness of sides (1)	Maximum deviation	± 1%	
Orthogonality (1)	Maximum deviation	± 1%	
Surface flatness (1)	Central curvature with respect to the diagonal	± 1.5%	
	Lateral curvature	± 1.5%	
	Warping with respect to the diagonal	± 1.5%	
Surface appearance	Tiles free of visible defects that could damage the	0501	
	appearance of a larger area of tile	95%	
Water absorption	Average	3% <e<6%< td=""><td rowspan="2">10.545-3</td></e<6%<>	10.545-3
	Individual maximum value	5%	
Breaking strength	Minimum value	2,000 N	10.545-4
Flexion resistance	Individual minimum value	14 N/mm ²	
	Average minimum value	16 N/mm ²	
Abrasion resistance	Maximum value	500 mm ³	10.545-6
Linear thermal expansion	Value	<4x10 ⁻⁶ /°C	10.545-8
Thermal shock resistance	Without visible defects	Correct	10.545-9
Frost resistance	Without visible defects	Correct	10.545-12
Chemical resistance	Cleaning products	UA	10.545-13
	Salts of swimming pools	UA	
	Acids and bases with weak concentration	ULA	
	Acids and bases with strong concentration	UHA	
Slipperiness	Average - CRD	>45	NLT 175/98
		(Class 3)	(UNE-ENV
Reaction to fire	Euroclass	A1	12633:2003)
Reaction to the	Darociass	Λ_1	